



General Information

| | |
|---------------------|------------------------------|
| Dimensions (mm) | 90 (W) x 120 (D) x 240 (H) |
| Materials | Body: Powdercoated Aluminium |
| Finish | Black (RAL9011) |
| Product Weight (Kg) | 1.05 |
| Ingress Protection | IP54 |
| Mounting | Wall |
| Warranty (Years) | 3 |

Supply & Power Information

| | |
|-------------------------------------|----------------------------------|
| Input Voltage & Frequency (V~ / Hz) | 230 50/60 |
| Safety Class | I |
| Circuit Wattage (W) | 2 x 6 (12) |
| LED Wattage (W) | 2 x 6 (12) |
| Inrush Current/Time | <10A (<0.5s) |
| Power Factor | >0.9 |
| Operating Temperature (°C) | -20 to +40 |
| Critical Temperature (°C) | +80 |
| Driver Information | Integrated |
| Input Terminations | Terminal Block (Screw Terminals) |

Luminaire Output

| | |
|----------------------------|-------------------|
| Colour Temperature (K) | 3000 |
| Colour Render Index (CRI) | >80 |
| Typical Luminous Flux (lm) | 2 x 436 (872) |
| Efficacy (lm/W) | 73 |
| Beam Angle (°) | 60 (Top & Bottom) |
| Flicker Free | Yes |
| LED Lifetime (L70) (Hours) | 50,000 |

Dimming Information

| | |
|----------|----|
| Dimmable | No |
|----------|----|

