


### General Information

Dimensions (mm)	300 (Dia.) x 20.5 (D)
Materials	Body: Powdercoated Aluminium; Diffuser: Polystyrene; Light Guide Plate (LGP): Polystyrene
Finish	White (RAL 9003)
Product Weight (Kg)	0.64
Cutout Diameter (mm)	285
Recess Depth Without Driver (mm)	16
Ingress Protection	IP44
Maximum Ceiling Thickness (mm)	32
Warranty (Years)	3

### Compatible Accessories

OVCGMF0004 - 240V~ 24-48W Multi-function Dimmable Constant Current LED Driver



### Supply & Power Information

Input Voltage & Frequency (V~ / Hz)	220-240 50/60
Safety Class	II
Circuit Wattage (W)	24
Input Current (mA)	280
Inrush Current/Time	3A (<5ms)
Power Factor	>0.5
Operating Temperature (°C)	-20 to +40
Critical Temperature (°C)	+45
Driver Information	Remote Driver Supplied
Prewired Flow™ Connector	3 Pole CT105-F Push-fit Terminals

### Luminaire Output

Colour Temperature (K)	4000
Colour Render Index (CRI)	>80
Typical Luminous Flux (lm)	1800
Efficacy (lm/W)	75
Beam Angle (°)	120
Energy Classification	G
LED Lifetime (L70) (Hours)	20000

### Dimming Information

Dimmable	No
----------	----

